




- Hydraulic buffer
- Opening angle: 105 °
- Diameter of hinge cup: 35mm
- Height of hinge cup 11.5mm
- Distance of door drilling: 3-7mm
- Distance of cup holes center: 48mm
- Door thickness: 14-21mm
- Finishing: Nickel plated
- Main material: Cold-rolled steel
- Material thickness: 0.8 - 1.2 - 1.2 mm
- Packing: 50 pairs




F4
Full Overlay



D	H	K	3	4	5	6	7
0			16	17	18	19	20
3			13	14	15	16	17
5			11	12	13	14	15




H4
Half Overlay



D	H	K	3	4	5	6	7
0			7	8	9	10	11
3			4	5	6	7	8
5			2	3	4	5	6



i4
Half Overlay




D	H	K	3	4	5	6	7
0			-2.5	-1.5	-0.5	0.5	1.5
3			-5.5	-4.5	-3.5	-2.5	-1.5
5			-7.5	-6.5	-5.5	-4.5	-3.5



- Hydraulic buffer
- Opening angle: 105 °
- Diameter of hinge cup: 35mm
- Height of hinge cup 11.5mm
- Distance of door drilling: 3-7mm
- Distance of cup holes center: 48mm
- Door thickness: 14-21mm
- Finishing: Nickel plated
- Main material: Cold-rolled steel
- Material thickness: 0.8 - 1.2 - 1.2 mm
- Packing: 50 pairs




FF4
Full Overlay



D \ H \ K	3	4	5	6	7
0	16	17	18	19	20
3	13	14	15	16	17
5	11	12	13	14	15



HF4
Half Overlay



D \ H \ K	3	4	5	6	7
0	7	8	9	10	11
3	4	5	6	7	8
5	2	3	4	5	6