





- Hydraulic buffer
- Opening angle: 105 °
- Diameter of hinge cup: 35mm
- Height of hinge cup 11.5mm
- Distance of door drilling: 3-7mm
- Distance of cup holes center: 48mm
- Door thickness: 14-21mm
- Finishing: Nickel plated
- Main material: Cold-rolled steel
- Material thickness: 0.8 - 1.2 - 1.2 mm
- Packing: 50 pairs

F4
Full Overlay




| D | H | K | 3 | 4 | 5 | 6 | 7 |
|---|---|---|----|----|----|----|----|
| 0 | | | 16 | 17 | 18 | 19 | 20 |
| 3 | | | 13 | 14 | 15 | 16 | 17 |
| 5 | | | 11 | 12 | 13 | 14 | 15 |

H4
Half Overlay



| D | H | K | 3 | 4 | 5 | 6 | 7 |
|---|---|---|---|---|---|----|----|
| 0 | | | 7 | 8 | 9 | 10 | 11 |
| 3 | | | 4 | 5 | 6 | 7 | 8 |
| 5 | | | 2 | 3 | 4 | 5 | 6 |

i4
Inset



| A | H | K | 3 | 4 | 5 | 6 | 7 |
|---|---|---|------|------|------|------|------|
| 0 | | | -2.5 | -1.5 | -0.5 | 0.5 | 1.5 |
| 3 | | | -5.5 | -4.5 | -3.5 | -2.5 | -1.5 |
| 5 | | | -7.5 | -6.5 | -5.5 | -4.5 | -3.5 |